

SafeScape S9000 Specifications

S9000 - G – One Egress Door – Sterling Gray Finish

Finish: After completion of fabrication, clean all metal surfaces to remove dirt and chemically treat to provide for paint adhesion. Curtain assembly is to receive a prime coat finish of .2 mils of epoxy primer and .8 mils of polyester paint in a McKeon Sterling Gray finish.

S9000 – PC – One Egress Door – Powder coat finish of colour as selected

Finish: After completion of fabrication, clean all metal surfaces to remove dirt and chemically treat to provide for powder coat adhesion. Provide powder coat finish of color as selected by architect from manufacturer's standard RAL powder coat selection chart.

S9000 – SS – One Egress Door – Stainless Steel No.4 Polished Finish

Finish: After completion of fabrication, clean all metal surfaces to remove dirt. All steel components shall receive two coats of rust inhibitive primer. All exposed stainless steel components shall be of type 304 with number 4 polish finish.

S9000 - G – Two Egress Doors – Sterling Gray Finish

Finish: After completion of fabrication, clean all metal surfaces to remove dirt and chemically treat to provide for paint adhesion. Curtain assembly is to receive a prime coat finish of .2 mils of epoxy primer and .8 mils of polyester paint in a McKeon Sterling Gray finish.

S9000 – PC – Two Egress Doors – Powder coat finish of colour as selected

Finish: After completion of fabrication, clean all metal surfaces to remove dirt and chemically treat to provide for powder coat adhesion. Provide powder coat finish of color as selected by architect from manufacturer's standard RAL powder coat selection chart.

S9000 – SS – Two Egress Doors – Stainless Steel No.4 Polished Finish

Finish: After completion of fabrication, clean all metal surfaces to remove dirt. All steel components shall receive two coats of rust inhibitive primer. All exposed stainless steel components shall be of type 304 with number 4 polish finish.